



9' x 7' 3285 white with optional white aluminum full-view window section

These models are also available in



# DURABLE. RELIABLE.

## SPECIFICATIONS, OPTIONAL FEATURES AND ACCESSORIES



### EXHAUST PORT

An exhaust port is an optional feature to keep those unwanted fumes from lingering around the work area.



### INSIDE SIDE LOCK

The inside side lock is a wise decision for added security when you are not around. (Torsion only)

### OPTIONAL WINDOW DESIGNS

24" SECTION HEIGHT



24" x 6"



24" x 12"



34" x 16"



Full-View

COLOR SELECTION

WHITE\*

ALMOND

SANDSTONE

BROWN

GRAY

BLACK

Note: Refer to samples at your local C.H.I. Distributor for exact color match.

\*3282 available in white only.



Wind chamber tested to ensure wind load resistance, the C.H.I. Windbreaker Series and iSeries doors provide enhanced defense against the elements.

FEATURES

26-GAUGE **MODEL 3285** Insulated

24-GAUGE **MODEL 3282** Insulated

### SECTIONS

- Features four evenly spaced micro-grooves that run horizontally across each section
- Double-sided steel doors are 24 or 26-gauge front and 27-gauge back for sturdiness
- Concealed steel back-up plates run from top to bottom of each section for secure hardware attachment
- Section joints are tongue-and-groove
- White painted end stiles
- Bottom "U" type astragal is a standard feature
- 3285 is available in white, almond, sandstone, brown, gray, or black; 3282 is available in white only

### TRACKS

- Tracks are 2" or 3", as specified
- Available in bracket mount, angle mount, clip angle mount, 12" radius, 15" radius, high lift, vertical lift, roof pitch, or dual track low headroom

### HARDWARE

- Package includes 11-gauge or 14-gauge hinges, as specified
- 2" or 3" long-stem or short-stem steel ball bearings rollers
- Heavy-duty adjustable top roller brackets

### SPRINGS

- Torsion springs are helically wound with stress relieved, oil-tempered wire
- Springs are individually-calibrated for each door
- Counter-balance torsion shafts are galvanized for rust resistance
- High cycle spring options may be specified

### INSULATION TYPE

- CFC free polystyrene core is secured in place with a urethane adhesive to increase structural integrity
- R-value - 10.29

VISIT YOUR DOOR PROFESSIONAL AT:

C.H.I. Overhead Doors are manufactured in Arthur, Illinois, USA.



### DOOR CONSTRUCTION

CFC free polystyrene insulation is secured in place with a urethane adhesive to increase structural integrity. The front and back skins are locked together in a tongue and groove design for years of worry free protection.

Model 3285..... R-value\* - 10.29

\*R-value testing is in accordance with ASTM C518 standards.